



SAFE-T-WHIP



Safe-T-Whip™ RD-2-01

The Regular Duty RD-2-01 is designed for the extreme Canadian weather and oil patch conditions. Lighter and more durable than steel cable, the RD-2-01 is our mid-ranged Safe-T-Whip.

Light weight, easy to haul, the RD-2-01 makes securing small diameter, high pressure flowlines, simply safe.

Impervious to oil and water conditions, or most chemicals, it is easy to hose off and simple to roll-up back into a tote.

*Easy to Set-up, Easy to Take-down
Safety couldn't be more convenient.*

IRON SIZE	
2" - 50mm	15,000PSI - 103 MPa
3" - 75mm	10,000PSI - 69 MPa

Simply loop the 4' (1.2m) RD-2-01 on one side of your hammer joint or swivel, then add a half-hitch to the other side. Make your connection, tighten and adjust as necessary. Changes are just as easy. Your joint, and the attached flowline pipe, is now protected from any lateral whip, should a pressurized joint failure occur.

Safe-T-Whip restraints are made HMPE (High Modulus Polyethylene) 12 strand rope, for use in the extreme hot and cold Canadian oilfield environment. It is a fibre that has high tensile strength, very low stretch characteristics, with excellent abrasion resistance, high UV resistance and long tension-to-tension fatigue life.

780.987.4442

Safe-T-Whip & Restraints Inc.
Box 5341, Leduc, AB Canada T9E 6L7
B-8906 92St. Grande Prairie, AB Canada T8V 7Y7
safetwhip@gmail.com